

Filters for the process industry



Masterfilter



Masterfilter was created in 2010. Competence in processes and utilization are the strenghts of Masterfilter.

We bring solutions for all kind of critical applications.

Masterfilter is a filtration company that focuses on high end solutions in PES & PTFE membrane filters and various pleated filter cartridges. Masterfilter provides professional technical and scientific assistance to filtration, separation and purification solutions. Our goal is to deliver innovative quality products on time with a high cost saving potential.

The philosophy of Masterfilter

Experience
Market and customer oriented
Flexible
Team spirit
High qualified engineers
Stable and independent
Very competitive
Find best fitting solution





Food and Dairy

Activated Carbon Filter

ACF



- Ideal for chlorine reduction
- Excellent absorbency
- · No release of active carbon
- Available in 2 grades
- FDA approved

Applications

- De-chlorination of process water and drinking water
- De-chlorination of drinking water
- De-chlorination of rinsing water
- De-colourisation

Melt blown depth filter

MBK



- · Three layer construction
- Thermal bonding without binders and adhesives
- High dirt holding capacity and long service life
- Removal rating (μm) : 1,0 – 150 μm

Applications

- · Pre-filtration for water
 - Pre-filtration for RO plants
- Beverage filtration

High flow filter cartridge

HCF



- High surface area
- High flow rate / smaller filter systems
- Coreless construction to minimize waste disposal
- Inside to outside flow configuration
- Absolute rated filter medium
- Available in 20"-40"-60" lenghts

Applications

- Water treatment
- Process water
- DI water

Multi-layer pleated polypropylene cartridge

APK



- Multi layers melt-blown polypropylene
- High dirt capacity
- 100 % polypropylene
- Absolute micron rating (μm) : 0,3 10 μm
- Retention of particles
- Reduction of bioburden from liquids

Applications

Pre-filtration for water and gases

Nano-fiber polypropylene pleated filter cartridge

۸DE



- High flow rate
- High dirt capacity
- Back washable, extend service life
- Micron rating (μm): 0,3 20 μm
- Absolute micron rating (μm) : 1,5 10 μm

Applications

- Water clarification
- Pre-filtration for RO plants

Hydrophilic polyethersulfone membrane

PES



- Easy wetting
- Low adsorption
- Repeatedly integrity testable
- Micron rating (μm) : 0,1 1,2 μm

Applications

Sterile water filtration





Sterile PTFE membrane gas filter

SLF-T



- Permanently hydrophobic PTFE membrane
- Suitable for all integrity test procedures
- Pleated surface for high flow rate and long life
- Removal rating (μm) : 0,2 μm

Applications

- Sterile filtration of air and CO₂
- Aseptic tank venting
- Process gas filtration
- Fermentor tank venting

Glass micro fibre cartridges

SLF-G



- Steam sterilisable
- High dirt holding capacity
- Pleated surface for high flow and low pressure drop
- Removal rating (μm) : 0,01, 0,3, 0,5 μm

Applications

- Sterile filtration of air and CO₂
- Aseptic tank venting
- Process gas filtration
- Membrane pre-filter
- Fermentor tank venting

Optivent SLV membrane vent filter

SLV



- Hydrophobic PTFE membrane
- Suitable for all integrity test procedures
- Pleated surface for high flow rate and long life
- Removal rating (μm): 0,2 μm

Applications

- Sterile venting of transport containers
- Sterile tank venting
- Sterile gas filtration

Stainless steel sintered filter cartridges

SDF



- Available in 316 stainless steel
- Cleanable and re-usable
- · Welded construction
- High temperature and corrosive resistant
- Removal rating (μm) : 1 100 μm

Applications

- Steam filtration (culinary)
- Aggressive chemicals and gases
- Viscous fluids
- Corrosive fluids

Housing range for liquids and gases

FG-F/G



- Manufactured in accordance with European regulations
- Supplied with a wide range of connections
- Mechanically / electro polishing
- Surface finish Ra < 0,8 μm
- Sanitary / industrial

Applications

- Liquid filtration
- Gas filtration
- Vent filtration

Filter integritiy tester

IT-01B



- Integrity testing for all membrane filters
- Single and multiple test
- Liquid and gas filter
- Compact design

Applications

- Bubble point test
- Pressure decay test
- WIT (optional)

Masterfilter Tell

Belgium

Masterfilter Belgium

Groddeweg 14 /A B-3010 KESSEL-LO Belgium

info@masterfilter.be www.masterfilter.eu Tel: +32 13 67 09 04 Fax: +32 13 67 09 01

The Netherlands

Masterfilter Nederland

W.J. van der Hooftstraat 18 4194 WD Meteren The Netherlands

info@masterfilter.nl www.masterfilter.nl Tel: +31 345 50 83 96

Germany, Austria & Schweiz

Masterfilter Deutschland

D-81827 München Germany

info@masterfilter.de www.masterfilter.eu Tel: +49 89 2885 8787 Fax: +49 89 2885 8788

Your local distributor

